

DC-35

For Earth, For Life
Kubota

Combine Harvester *For Rice*



COMPACT YET FULLY FEATURED

OUTSTANDING FEATURES

- IDEAL FOR HARVESTING SMALL PADDY FIELDS
- OUTSTANDING THRESHING AND SEPARATION PERFORMANCES
- EXCEPTIONAL OPERATIONAL PERFORMANCE UNDER HIGH LOAD CONDITIONS
- EASY OPERATION
- EASY MAINTENANCE

Exceptional Operational Performance



SPECIFICATIONS

Dimensions	Length		mm	4120
	Width		mm	1850
	Height		mm	2150
Weight			kg	1550
Engine	Model			Kubota D1105-T-E2-C-1
	Type			Water-cooled, 4-Cycle, 3-Cylinder, Vertical Diesel Engine (with Turbocharger)
	Displacement		L	1.123
	Output/Rotation Speed		kW(PS)/rpm	24.5 (33.3) / 3000
	Fuel Tank Capacity		L	60
Travel Section	Crawler	Width x Ground Contact Length	mm	400 x 1330
		Center Distance	mm	940
		Average Ground Pressure	kPa(kgf/cm ²)	14.3 (0.146)
		Minimum Ground Clearance	mm	300
	Speed Shift System			Hydrostatic Variable Speed (HST)
	Travel Speed	Forward	m/s	Low: 0 - 0.70
		Backward	m/s	High: 0 - 1.10
Turning System			Clutch and Break	
Reaper Section	Reel	Diameter x Width	mm	800 x 1420
		Up/Down Control		Hydraulic System
	Cutter Bar Length	mm	1448	
Thresher Section	Threshing System			Axial Flow System (Threshing Tooth System)
	Threshing Cylinder	Diameter x Length	mm	545 x 1520
		Revolutions	rpm	630
	Concave Area		m ²	0.991
Sorting System			Oscillating / Wind Force (Adjustable Chaffer Sieve)	
Hopper	Capacity		L	130
	Take-out System			2 / Bagging
Electrical System				12 Volts Battery Starting, Lighting Equipment, and Alarms (Coolant Temperature, Engine Oil Pressure, & Hopper Full)
Harvesting Capacity			ha/hr	0.1 - 0.27 (Rice)

KUBOTA Philippines, Inc.

Manila Head Office:

232 Quirino Highway, Baesa, Quezon City, Metro Manila
Tel. Nos.: (632) 4223500 to 03; Fax Nos.: (632) 4223504 to 05
E-mail: kpi@kubota.com.ph

Davao Branch:

1 Yuta@Dabaw Bldg., Purok 38, Diversion Road, Ma-a, Davao City 8000
Tel. Nos.: (082) 2828160 to 61
E-mail: kpidavao@kubota.com.ph

Website: www.kubota.com.ph

Authorized Dealer: