

For Earth, For Life
Kubota

KUBOTA DIESEL TRACTOR

L

L5018

All the power and versatility you need to handle any job,
from paddy to dry fields.



Specifications

Model	L5018		
Engine			
Maker	Kubota		
Model	V2403-M-DI		
Type	Direct injection, Vertical, Water-Cooled 4 cycle diesel		
Engine gross power	HP	50	
Engine net power	HP	47	
Number of cylinders	4		
Bore and stroke	mm	87 x 102.4	
Total displacement	ℓ	2.434	
Rated revolution	rpm	2700	
Maximum torque	N-m	155	
Fuel Tank	ℓ	48	
PTO			
Rear PTO	SAE 1-3/8, 6-splines		
PTO / Engine speed	rpm	540 (2268), 750 (2348)	
Hydraulic system			
Hydraulic control system	Position control		
Pump capacity (main)	ℓ/min.	30.5	
3-point hitch	Category I		
Max. lift force	At lift points	kg	1300
	610 mm behind	kg	1053
Traveling System			
Tires	Front	8 - 18	
	Rear	13.6 - 26	
Clutch	Dry type Single stage		
Power Steering	Standard (Integral)		
Transmission	Gear shift, 8 forward and 8 reverse		
Shuttle	Synchro-shuttle		
Brake	Wet disk type		
Min. turning radius (with brake)	m	2.65	
Traveling speed	Forward	km/h	2.5 - 27.2
	Reverse	km/h	2.4 - 26.1
Dimensions			
Overall length (without 3P)	mm	3200	
Overall width	mm	1495	
Overall height	mm	2049	
Wheelbase	mm	1925	
Min. ground clearance	mm	400	
Tread	Front	mm	1150
	Rear	mm	1155, 1225
Weight	kg	1490	

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Please contact your local Kubota dealer for warranty information. The operator's manual should be consulted for more complete operational information.

Kubota Philippines, Inc.

Manila Head Office:

232 Quirino Highway, Baesa, Quezon City,
Metro Manila
Tel. Nos.: (632) 4223500 to 03
Fax Nos.: (632) 4223504 to 05
E-mail: kpi@kubota.com.ph
Website: www.kubota.com.ph

Davao Branch:

1 Yuta@Dabaw Bldg.,
Purok 38, Diversion Road,
Ma-a, Davao City 8000
Tel. Nos.: (082) 2828160 to 61
E-mail: kpidavao@kubota.com.ph

Authorized Dealer:

